

*In the Claims*

1. (CANCELLED)
2. (CANCELLED)
3. (CANCELLED)
- 5 4. (CANCELLED)
5. (CANCELLED)
6. (CANCELLED)
7. (CANCELLED)
8. (CANCELLED)
- 10 9. (CANCELLED)

10. (TWICE AMENDED) A base lid comprising in combination:

- a body having a bottom wall and a side wall;
- said side wall having an interior surface and exterior surface, the interior surface of the
- 15 wall defining the opening;
- said body consisting of a tab positioned on the side of the body;
- the defining opening created by the body, side wall, and bottom defining a round
- opening.;
- an interior wall with recessed and protruding areas;
- 20 said interior wall thickness increases at a linear slope rate from the lid opening toward the
- bottom of the base lid defining an angular slope toward the exterior wall and defining a
- protrusion at a small radial arc, said interior wall thickness then decreases at a linear rate
- defining an angular slope toward the exterior wall, and then remains at a constant wall

thickness until the base wall is reached;

said linear rate creating an interior protrusion is between 10 degrees and 20 degrees.

11. (CANCELLED)

5 12. (CANCELLED)

13. (CANCELLED)

14. (CANCELLED)

15. (CANCELLED)

16. (CANCELLED)

10